

MARLOWE
FIRE & SECURITY

Compliance. Assured.





Contents

2	Commander Fire Extinguishers
12	CommanderEDGE Fire Extinguishers
24	Contempo Fire Extinguishers
32	Trolleys and Covers
34	Stands
36	Cabinets
37	Signs
40	Alarms
41	Fire Protection Products



Free hose
Aim nozzle
at base of fire



Squeeze handles



Tested to BS EN3-7. Safe for inadvertent use on live electrical fires up to 1000V

CAUTION:

Depressurise and recharge after any use.
Check weight at least once a year.
Protect from frost.

COMMANDER®

CheckFire Ltd, Caerphilly, CF83 3HU



BS EN3
KM 5000



RECHARGE AFTER USE
THIS EXTINGUISHER SHOULD
SERVICED AT LEAST ONCE
A QUALIFIED COMPETENT
ACCORDANCE WITH BS
RECHARGING SHOULD BE
OUT TO BS 6643 PART 1
COMPONENTS RECOMMENDED
THE MANUFACTURER

MODEL WSWX6 (W6)
EXTINGUISHER MEDIUM
OPERATING TEMPERATURE
TEST PRESSURE 27 BAR
PRESSURISING GAS NITROGEN



With one of the widest ranges available on the market today, Commander is firmly regarded as a true market leader.

Time has proved these portable fire extinguishers as a dependable choice for almost any situation and reliable performance is guaranteed. What's more, the 6ltr/kg and 9ltr/kg units now carry the BSI Kitemark certification.

Commander Water Fire Extinguishers

A water-based fire extinguisher is a popular choice for Class A fires (combustible materials). Water fire extinguishers work by cooling the fuel and ensuring it burns at a much slower pace until the fire is extinguished.

Most premises are required to have a water or foam extinguisher - they're often found in busy places like offices, schools and hospitals. With a low-cost price and ease of maintenance, it's easy to see why water fire extinguishers are a preferred choice for many businesses. The Commander range of water fire extinguishers benefits from the following:

Features

- Kitemarked* and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty**
- MED approval on selected products



3ltr Water Compact PLUS

CODE	WSEX3A
CAPACITY	3 LITRE
FIRE RATING	13A
EXTINGUISHER MEDIUM	WATER + ADDITIVE
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN

6ltr Water PLUS Spray

CODE	WSWX6
CAPACITY	6 LITRE
FIRE RATING	21A
EXTINGUISHER MEDIUM	WATER + ADDITIVE
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN



9ltr Water PLUS Spray

CODE	WSWX9
CAPACITY	9 LITRE
FIRE RATING	27A
EXTINGUISHER MEDIUM	WATER + ADDITIVE
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN





Commander Foam Fire Extinguishers

Most commonly used on Class B fires (flammable liquids), a foam fire extinguisher is also a recommended choice for Class A risk areas (those featuring combustible materials). These extinguishers perform a cooling function and quickly smother burning materials, while the foam agent helps prevent the fire reigniting.

Foam fire extinguishers shouldn't be used on kitchen fires or those with an electrical source. However, they're ideal for office environments, hospitals, schools and other spaces where organic materials play a large role in the landscape. The Commander range of foam fire extinguishers benefits from the following:

Features

- Kitemarked* and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty**
- MED approval on selected products



**1ltr
AFF Foam**

CODE FSEX1
CAPACITY 1 LITRE
FIRE RATING 5A 21B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**3ltr
AFF Foam**

CODE FSEX3
CAPACITY 3 LITRE
FIRE RATING 13A 55B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 12 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**6ltr
AFF Foam**

CODE FSWX6
CAPACITY 6 LITRE
FIRE RATING 21A 144B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**9ltr
AFF Foam**

CODE FSWX9
CAPACITY 9 LITRE
FIRE RATING 27A 183B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN





Commander Powder Fire Extinguishers

A dry powder fire extinguisher is extremely versatile. It's suitable for use on Class A (combustible materials), Class B (flammable liquids) and Class C (flammable gases) fires. It's for this reason they're known as 'ABC' extinguishers. This extinguisher smothers fires by producing a thick barrier between the fuel and the source of oxygen.

A powder fire extinguisher shouldn't be used in confined spaces because the powder can easily be inhaled and it leaves a residue that can be difficult to clean up. Consider this extinguisher for premises including garage forecourts, commercial boiler rooms and workspaces that feature welding. The Commander range of powder fire extinguishers benefits from the following:

Features

- Kitemarked* and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty**
- MED approval on selected products

		
3kg ABC Dry Powder	6kg ABC Dry Powder	9kg ABC Dry Powder
CODE DPEX3	CODE DPWX6	CODE DPWX9
CAPACITY 3KG	CAPACITY 6KG	CAPACITY 9KG
FIRE RATING 13A 89B C	FIRE RATING 43A 223B C	FIRE RATING 55A 233B C
EXTINGUISHER MEDIUM ABC 40	EXTINGUISHER MEDIUM ABC 30	EXTINGUISHER MEDIUM ABC 30
WORKING PRESSURE 14 BAR	WORKING PRESSURE 14 BAR	WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL	CYLINDER MATERIAL STEEL	CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN	PRESSURING GAS NITROGEN	PRESSURING GAS NITROGEN
	 	 



FIRE ALARM



COMMANDER

Water
PLUS

FIRE EXTINGUISHER
9 Litre WATER SPRAY PLUS
27A

For use on fire, paper, timber and other
Class A fires

- Use upright
Pull out safety pin
- Free hose
Aim nozzle
at base of fire
- Squeeze handles



CE mark

COMMANDER

Powder

FIRE EXTINGUISHER
12kg ABC POWDER
12kg ABC

For use on fire, paper, timber and other
Class A, B and C fires

- Use upright
Pull out safety pin
- Free hose
Aim nozzle
at base of fire
- Squeeze handles



CE mark

COMMANDER

Commander

Wet Chemical Fire Extinguishers

A wet chemical fire extinguisher is specifically designed for use on Class F fires (cooking oils and fats), making it the ideal solution for the demands of commercial kitchen and canteen environments.

This type of extinguisher works by creating a layer of foam on the burning oil or fat, stopping the supply of oxygen so the fire isn't fuelled any further. Available in a choice of sizes, find the ideal wet chemical fire extinguisher for your requirements. The Commander range of wet chemical fire extinguishers benefits from the following:

Features

- Manufactured to BS EN3
- Corrosion-resistant cylinders
- Polyethylene internal lining
- Full range of spare parts available
- Easy-clean design



3ltr Wet Chemical

CODE	WCEX3
CAPACITY	3 LITRE
FIRE RATING	8A 75F
EXTINGUISHER MEDIUM	WET CHEMICAL
WORKING PRESSURE	7 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STAINLESS STEEL
PRESSURING GAS	NITROGEN

6ltr Wet Chemical

CODE	WCEX6
CAPACITY	6 LITRE
FIRE RATING	13A 75F
EXTINGUISHER MEDIUM	WET CHEMICAL
WORKING PRESSURE	7 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STAINLESS STEEL
PRESSURING GAS	NITROGEN



1
All food must be covered and dated



COMMANDER



**Free hose
Aim nozzle
at base of fire**



Squeeze handles



WARNING:
Do not use on liquid fires or live electrical equipment
Depressurise and recharge after any use
Check weight at least once a year
Protect from frost

For use on wood, paper, textile and similar
Class A fires.

COMMANDER EDGE

CHECKFIRE, Pontywindy Industrial Estate, Caerphilly, UK, CF83 3HU



RECHARGE AFTER USE
THIS EXTINGUISHER SHOULD
SERVICED AT LEAST
A QUALIFIED COMPETENT
ACCORDANCE WITH BS
RECHARGING SHOULD
OUT TO BS 6843 PART 1
COMPONENTS RECOMMENDED
THE MANUFACTURER

MODEL WS 9E (10)
EXTINGUISHER MEDIUM WATER
OPERATING TEMPERATURE
TEST PRESSURE 30 BAR WITHOUT
PRESSURISING GAS WITHIN



With one of the widest ranges available on the market today, CommanderEDGE is firmly established as the market leader.

The range is fully Kitemarked by BSI and is the choice of the professional with its reassuring mixture of performance, quality and value.

CommanderEDGE

Water Fire Extinguishers

Ideal for Class A fire risk areas (those featuring combustible materials), water-based extinguishers remain a popular choice for many businesses. Pointed at the base of the fire, this extinguisher releases water to cool the fuel, ensuring it burns at a slow pace until it's completely extinguished.

CommanderEDGE extinguishers prioritise high performance, superb quality and unrivalled value. Available in six-litre and nine-litre units, CommanderEDGE water fire extinguishers come with a five-year warranty. What's more, the 6ltr Water Compact 34, with additive, boasts a remarkable 34A fire rating, making it an exceptional powerhouse for its light weight. The CommanderEDGE range of water fire extinguishers benefits from great design, a strong plastic base skirt and the following:

Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty*
- MED approval on selected products



**6ltr
Water**

CODE	WS6E
CAPACITY	6 LITRE
FIRE RATING	13A
EXTINGUISHER MEDIUM	WATER
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN



**6ltr Water
Compact 34**

CODE	WS6EA
CAPACITY	6 LITRE
FIRE RATING	34A
EXTINGUISHER MEDIUM	WATER
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN



**9ltr
Water**

CODE	WS9E
CAPACITY	9 LITRE
FIRE RATING	13A
EXTINGUISHER MEDIUM	WATER
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN





CommanderEDGE Foam Fire Extinguishers

This type of extinguisher is an ideal choice for Class A and B risk areas (those featuring combustible materials and flammable liquids). A foam extinguisher performs a cooling function, while a layer of foam floats on top of the burning liquid to prevent reignition.

CommanderEDGE extinguishers prioritise high performance, superb quality and unrivalled value. Available in two-litre, six-litre and nine-litre units, CommanderEDGE foam extinguishers are a robust and reliable solution for tackling Class A and B fires. Plus, for the environmentally conscious, EnviroFoam's low fluorine content ensures it's less harmful to the environment than regular foams. The CommanderEDGE range of foam fire extinguishers benefits from great design and the following:

Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty*
- MED approval on selected products



**2ltr
AFF Foam**

CODE FS2E
CAPACITY 2 LITRE
FIRE RATING 8A 55B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5-+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**6ltr
AFF Foam**

CODE FS6E
CAPACITY 6 LITRE
FIRE RATING 13A 144B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5-+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**6ltr
EnviroFoam**

CODE FS6ECO
CAPACITY 6 LITRE
FIRE RATING 27A 183B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5-+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**9ltr
AFF Foam**

CODE FS9E
CAPACITY 9 LITRE
FIRE RATING 21A 183B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5-+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



EniroFoam

Foam

FIRE EXTINGUISHER

6 Litre FOAM SPRAY
27A 183B

For use on burning liquid fires (Class B) and
wood, paper, textile and similar Class A fires



Use upright
Pull out safety pin



Free hose
Aim nozzle
At base of fire



Squeeze handles



CAUTION:

Tested to BS EN3-7 safe for inadvertent use on electrical fires.
Depressurise and recharge after any use.
Check weight at least once a year. Protect from frost

COMMANDER EDGE

CheckFire, Caerphilly, CF83 3HU

CommanderEDGE Powder Fire Extinguishers

A dry powder fire extinguisher is extremely versatile, suitable for use on Class A (combustible materials), Class B (flammable liquids) and Class C (flammable gases) fires. It's for this reason they're known as 'ABC' extinguishers.

This extinguisher smothers fires by producing a thick barrier between the fuel and the source of oxygen. A powder fire extinguisher shouldn't be used in confined spaces because the powder can easily be inhaled and it leaves a residue that can be difficult to clean up. Consider this extinguisher for premises including garage forecourts, commercial boiler rooms and workspaces that feature welding. This range benefits from the following:

Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty*
- MED approval on selected products



**1kg ABC
Dry Powder**

CODE
DP1E

CAPACITY
1KG

FIRE RATING
8A 34B C

EXTINGUISHER MEDIUM
ABC 40

WORKING PRESSURE
14 BAR

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**2kg ABC
Dry Powder**

CODE
DP2E

CAPACITY
2KG

FIRE RATING
13A 70B C

EXTINGUISHER MEDIUM
ABC 40

WORKING PRESSURE
14 BAR

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**4kg ABC
Dry Powder**

CODE
DP4E

CAPACITY
4KG

FIRE RATING
21A 89B C

EXTINGUISHER MEDIUM
ABC 40

WORKING PRESSURE
14 BAR

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6kg ABC
Dry Powder**

CODE
DP6E

CAPACITY
6KG

FIRE RATING
34A 233B C

EXTINGUISHER MEDIUM
ABC 40

WORKING PRESSURE
14 BAR

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**9kg ABC
Dry Powder**

CODE
DP9E

CAPACITY
9KG

FIRE RATING
55A 233B C

EXTINGUISHER MEDIUM
ABC 40

WORKING PRESSURE
14 BAR

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN





CommanderEDGE MultiCHEM Fire Extinguishers

For an innovative fire-fighting solution, choose the latest in high-performance multi-class extinguishers.

MultiCHEM is an ABF-rated extinguisher ideal for flammable liquid fires involving large quantities of fuel and a big surface area. But it's also suitable for deep fat fryer fires too.

The extinguisher's 34A rating – the industry's highest for a six-litre extinguisher – means that it's capable of tackling a sizeable fire. This ground-breaking extinguisher is also available in two and three litre sizes, as well as unique, aesthetically pleasing finishes, to perfectly tailor to your needs. This range benefits from the following:

Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty*
- MED approval on selected products



**2ltr
MultiCHEM**

CODE	FS2EMC
CAPACITY	2 LITRE
FIRE RATING	8A 70B 25F
EXTINGUISHER MEDIUM	FOAM
WORKING PRESSURE	12 BAR
TEMPERATURE RANGE	-5+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN



**3ltr
MultiCHEM**

CODE	FS3EMC
CAPACITY	3 LITRE
FIRE RATING	13A 89B 40F
EXTINGUISHER MEDIUM	FOAM
WORKING PRESSURE	12 BAR
TEMPERATURE RANGE	-5+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN



**6ltr
MultiCHEM**

CODE	FS6EMC
CAPACITY	6 LITRE
FIRE RATING	34A 233B 75F
EXTINGUISHER MEDIUM	FOAM
WORKING PRESSURE	12 BAR
TEMPERATURE RANGE	-5+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN





CommanderEDGE CO2 Fire Extinguishers

A carbon dioxide (CO₂) extinguisher is the perfect choice for Class B fires (those involving flammable liquids). However, it's also suitable for use on electrical fires because it won't damage electrical equipment or machinery. Carbon dioxide suffocates a fire and displaces oxygen in the air.

CommanderEDGE extinguishers prioritise high performance, superb quality and unrivalled value. These CO₂ extinguishers are among the finest on the market. Aluminium or alloy squat bodies (in the 2kg models) allow for ease of handling, while in the 5kg models, you can rely on a best-in-class 89B fire rating. The CommanderEDGE range of CO₂ fire extinguishers benefits from the following:

Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Distinctive black horn
- Full range of spare parts available
- Five-year warranty*
- MED approval on selected products

			
2kg CO2	5kg CO2	2kg CO2 Aluminium	5kg CO2 Aluminium
CODE CO2E	CODE CO5E	CODE CO2EA	CODE CO5EA
CAPACITY 2KG	CAPACITY 5KG	CAPACITY 2KG	CAPACITY 5KG
FIRE RATING 34B	FIRE RATING 70B	FIRE RATING 34B	FIRE RATING 89B
EXTINGUISHER MEDIUM CO2	EXTINGUISHER MEDIUM CO2	EXTINGUISHER MEDIUM CO2	EXTINGUISHER MEDIUM CO2
WORKING PRESSURE 56 BAR @ 20°C	WORKING PRESSURE 56 BAR @ 20°C	WORKING PRESSURE 56 BAR @ 20°C	WORKING PRESSURE 56 BAR @ 20°C
TEMPERATURE RANGE -20+60°C	TEMPERATURE RANGE -20+60°C	TEMPERATURE RANGE -20+60°C	TEMPERATURE RANGE -20+60°C
CYLINDER MATERIAL ALLOY STEEL	CYLINDER MATERIAL ALLOY STEEL	CYLINDER MATERIAL ALUMINIUM	CYLINDER MATERIAL ALUMINIUM
 	 	 	 





Use upright.
Pull out safety pin.



Free hose.
Aim nozzle at base of fire.



Squeeze handles.



CAUTION:

Do not use on live electrical equipment.
Despressurise and recharge after every use.
Check weight at least once a year.
Protect from frost.

CONTEMPO



A fire extinguisher is a vital piece of equipment and, for any space that particularly prides itself on its aesthetic, the Contempo range – an industry first – has arrived.

The very finest interior finishes are beautifully researched and designed. Contempo provides stunning hand-finished extinguishers to complement the most exquisite interior – and nine-litre models can be available on request.

Contempo Polished Gold

Synonymous with luxury, these hand-finished polished gold extinguishers serve as a stunning addition to elegant interiors.

Whether you are fitting out a stately home, palace or a castle, these extinguishers are a perfect solution. These are electro plated to give a stunning mirror finish. And with the matching polished gold tubular stands and ID signs, this range truly is elegance in fire defence. The Contempo range of Polished Gold fire extinguishers benefits from the following:

Features

- Manufactured to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- Five-year warranty*
- Super strong base skirt for protection
- Polyethylene internal lining (on water and foam units)
- 9ltr models available. More information on request.



**2kg CO2
Polished Gold**

CODE
COEX2PG

CAPACITY
2KG

FIRE RATING
34B

EXTINGUISHER MEDIUM
CO2

WORKING PRESSURE
56 BAR @ 20°C

TEMPERATURE RANGE
-20+60°C

CYLINDER MATERIAL
ALLOY STEEL



**6ltr AFF Foam
Polished Gold**

CODE
FSEX6PG

CAPACITY
6 LITRES

FIRE RATING
13A 144B

EXTINGUISHER MEDIUM
AFF FOAM

WORKING PRESSURE
14 BAR

TEMPERATURE RANGE
+5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6ltr MultiCHEM
Polished Gold**

CODE
FSEX6MCPG

CAPACITY
6 LITRES

FIRE RATING
34A 233B 75F

EXTINGUISHER MEDIUM
FOAM

WORKING PRESSURE
12 BAR

TEMPERATURE RANGE
-5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6ltr Water
Polished Gold**

CODE
WSEX6PG

CAPACITY
6 LITRES

FIRE RATING
13A

EXTINGUISHER MEDIUM
WATER

WORKING PRESSURE
14 BAR

TEMPERATURE RANGE
+5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6kg Powder
Polished Gold**

CODE
DPEX6PG

CAPACITY
6KG

FIRE RATING
34A 233B C

EXTINGUISHER MEDIUM
ABC 40

WORKING PRESSURE
14 BAR

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



Contempo Antique Copper

Truly an industry-first, these exquisite extinguishers have been hand-finished. Each one is unique in its beauty.

Perfect for modern bars and restaurants, luxury hotels and contemporary commercial interiors, this is fire safety equipment that deserves to be on show. And with the matching brushed Antique Copper tubular stands and ID signs, this range exudes elegance as well as providing all the practical features and meeting industry standards. This unique range benefits from the following:

Features

- Manufactured to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- Five-year warranty*
- Super strong base skirt for protection
- Polyethylene internal lining (on water and foam units)



**2kg CO2 Brushed
Antique Copper**

CODE
COEX2AC

CAPACITY
2KG

FIRE RATING
34B

EXTINGUISHER MEDIUM
CO2

WORKING PRESSURE
56 BAR @ 20 C

TEMPERATURE RANGE
-20+60°C

CYLINDER MATERIAL
ALLOY STEEL



**6ltr AFF Foam
Antique Copper**

CODE
FSEX6AC

CAPACITY
6 LITRES

FIRE RATING
13A 144B

EXTINGUISHER MEDIUM
AFF FOAM

WORKING PRESSURE
14 BAR

TEMPERATURE RANGE
+5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6ltr MultiCHEM
Antique Copper**

CODE
FSEX6MCAC

CAPACITY
6 LITRES

FIRE RATING
34A 233B 75F

EXTINGUISHER MEDIUM
FOAM

WORKING PRESSURE
12 BAR

TEMPERATURE RANGE
-5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6ltr Water
Antique Copper**

CODE
WSEX6AC

CAPACITY
6 LITRES

FIRE RATING
13A

EXTINGUISHER MEDIUM
WATER

WORKING PRESSURE
14 BAR

TEMPERATURE RANGE
+5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6kg Powder
Antique Copper**

CODE
DPEX6AC

CAPACITY
6KG

FIRE RATING
34A 233B C

EXTINGUISHER MEDIUM
ABC 40

WORKING PRESSURE
14 BAR

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



Contempo Stainless Steel

With a superb highly polished finish, luxury stainless steel extinguishers are perfect for areas where appearance is important.

Stainless steel is one of the most corrosion-resistant metals known, as well as being extremely strong. That means these units are among the toughest available and are proven to last – even in the harshest of environments. The Contempo range of Stainless Steel fire extinguishers benefits from the following:

Features

- Manufactured to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- Five-year warranty*
- Super strong base skirt for protection
- Polyethylene internal lining (on water and foam units)
- We also have 9ltrs available in the range



**2kg CO2
Stainless Steel**

CODE
COEX2P

CAPACITY
2KG

FIRE RATING
34B

EXTINGUISHER MEDIUM
CO2

WORKING PRESSURE
56 BAR @ 20°C

TEMPERATURE RANGE
-20+60°C

CYLINDER MATERIAL
ALLOY STEEL



**6ltr AFF Foam
Stainless Steel**

CODE
FSEX6SS

CAPACITY
6 LITRES

FIRE RATING
13A 144B

EXTINGUISHER MEDIUM
AFF FOAM

WORKING PRESSURE
14 BAR

TEMPERATURE RANGE
+5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6ltr MultiCHEM
Stainless Steel**

CODE
FSEX6MCSS

CAPACITY
6 LITRES

FIRE RATING
34A 233B 75F

EXTINGUISHER MEDIUM
FOAM

WORKING PRESSURE
12 BAR

TEMPERATURE RANGE
-5+60°C

CYLINDER MATERIAL
ALLOY STEEL

PRESSURE GAS
NITROGEN



**6ltr Water
Stainless Steel**

CODE
WSEX6SS

CAPACITY
6 LITRES

FIRE RATING
13A

EXTINGUISHER MEDIUM
WATER

WORKING PRESSURE
14 BAR

TEMPERATURE RANGE
+5+60°C

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



**6kg Powder
Stainless Steel**

CODE
DPEX6SS

CAPACITY
6KG

FIRE RATING
34A 233B C

EXTINGUISHER MEDIUM
ABC 40

WORKING PRESSURE
14 BAR

CYLINDER MATERIAL
STEEL

PRESSURING GAS
NITROGEN



GOOD
VIBES
ONLY

Trolleys and Covers

Fire extinguisher trolleys and covers help to protect vital fire fighting equipment from corrosion, accidental damage and misuse.



Double Trolley

CODE CS23
WEIGHT 16KG
DIMENSIONS (WHD) 1200 X 720 X 400MM
FIRE EXTINGUISHERS 2
ROBUST POWDER COATED STEEL FRAME
NYLON WHEELS
SPACE FOR FIRE BUCKET
SPACE FOR ALARM BELL / SITE ALARM
CAN BE ADAPTED TO HOLD CO2 FIRE EXTINGUISHERS



Compact Double Trolley

CODE CS23A
WEIGHT 14KG
DIMENSIONS (WHD) 1200 X 470 X 400MM
FIRE EXTINGUISHERS 2
ROBUST POWDER COATED STEEL FRAME
NYLON WHEELS
SPACE FOR FIRE BUCKET
SPACE FOR ALARM BELL / SITE ALARM
COMPACT, SPACE SAVING DESIGN



Backboard Double Trolley

CODE CS23-DF
WEIGHT 16KG
DIMENSIONS (WHD) 1200 X 720 X 400MM
FIRE EXTINGUISHERS 2
ROBUST POWDER COATED STEEL FRAME
NYLON WHEELS
SPACE FOR FIRE BUCKET
SPACE FOR ALARM BELL / SITE ALARM
A LARGE STEEL BACKBOARD FOR MOUNTING ALARM EQUIPMENT AND SIGNAGE



Mobile Fire Point Stand

CODE CS26A
WEIGHT 20KG
DIMENSIONS (WHD) 1800 X 890 X 480MM
FIRE EXTINGUISHERS 4
ROBUST POWDER COATED STEEL FRAME
NYLON WHEELS
SPACE FOR FIRE BUCKET
SPACE FOR ALARM BELL / SITE ALARM
A LARGE STEEL BACKBOARD FOR MOUNTING ALARM EQUIPMENT AND SIGNAGE
ALSO AVAILABLE IN YELLOW AND GREEN



PVC Extinguisher Cover (Medium)

CODE CS22
FITS UP TO 6KG / 6LTR FIRE EXTINGUISHERS
QUALITY PVC MATERIAL
CLEAR VIEWING WINDOW
VELCRO STRAPS TO ALLOW FOR EASE OF FITTING AND SECURING



PVC Extinguisher Cover (Large)

CODE CS21
FITS UP TO 9KG / 9LTR FIRE EXTINGUISHERS
QUALITY PVC MATERIAL
CLEAR VIEWING WINDOW
VELCRO STRAPS TO ALLOW FOR EASE OF FITTING AND SECURING



Fire
assembly point

FIRE ALARM



COMMANDER

Water

FIRE EXTINGUISHER
10 A

- Use upright
Pull out safety pin
- Free hose
Aim nozzle
at base of fire
- Squeeze handles

For use on all fires (Class A, B & C)
100% water based
100% water based
100% water based
100% water based

COMMANDER EDGE

Powder

FIRE EXTINGUISHER
10 A 10 B C

- Use upright
Pull out safety pin
- Free hose
Aim nozzle
at base of fire
- Squeeze handles



For use on all fires (Class A, B & C)
100% dry powder
100% dry powder
100% dry powder
100% dry powder

COMMANDER EDGE

Stands

Fire extinguisher stands are a versatile solution for display where wall-mounting might not be appropriate.



Single Tubular Stand

CODE CS30
WEIGHT 1.75KG
DIMENSIONS 840 X 390 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

*OPTIONAL



Double Tubular Stand

CODE CS31
WEIGHT 2.5KG
DIMENSIONS 840 X 500 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

*OPTIONAL



Single Tubular Stand

CODE CS32
WEIGHT 1.75KG
DIMENSIONS 840 X 390 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
AVAILABLE IN RED, STAINLESS STEEL, ANTIQUE COPPER AND POLISHED GOLD
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

*OPTIONAL



Double Tubular Stand

CODE CS33
WEIGHT 2.5KG
DIMENSIONS 840 X 500 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
AVAILABLE IN RED, STAINLESS STEEL, ANTIQUE COPPER AND POLISHED GOLD
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

*OPTIONAL



Commander Single Extinguisher Stand

CODE CS50
WEIGHT 1.2KG
DIMENSIONS 280 X 750 X 275MM
SUITABLE FOR MAX 200MM
RELIABLE AND ROBUST PP PLASTIC MATERIAL
COMBINATION OF BOTH A MATT AND GLOSS FINISH
DEDICATED AREA FOR SIGNAGE APPLICATION
GRIPPED BASE TO PROTECT FLOOR SURFACE
EASILY COMBINE TO MAKE A TRIPLE PLUS STAND
IMMEDIATE ACCESS TO THE FIRE EXTINGUISHER
ENVIRONMENTALLY FRIENDLY MATERIALS



Commander Double Extinguisher Stand

CODE CS51
WEIGHT 2.3KG
DIMENSIONS 548 X 750 X 288.5MM
SUITABLE FOR MAX 200MM
RELIABLE AND ROBUST PP PLASTIC MATERIAL
COMBINATION OF BOTH A MATT AND GLOSS FINISH
DEDICATED AREA FOR SIGNAGE APPLICATION
GRIPPED BASE TO PROTECT FLOOR SURFACE
EASILY COMBINE TO MAKE A TRIPLE PLUS STAND
IMMEDIATE ACCESS TO THE FIRE EXTINGUISHER
ENVIRONMENTALLY FRIENDLY MATERIALS



Wave Wall Extinguisher Stand

CODE WAVE/RED
WEIGHT 1.90KG
DIMENSIONS 386 X 234 X 400MM
SUITABLE FOR MAX DIAMETER 135-200MM
SOLID STRUCTURE FIVE FIXING POINTS
AVAILABLE IN RED AND WHITE



Cabinets

Safely store fire extinguishers in a cabinet that protects against accidental damage, misuse and all-weather conditions.



Single Commander Cabinet

CODE CS01DA9
CAPACITY 9KG/9LTR/2KG CO2
EXTERNAL DIMS (WHD) 335 X 715 X 240MM
INTERNAL DIMS (WHD) 264 X 652 X 204MM
FULLY WEATHER SEALED
RESISTANT TO CHEMICALS
BRILLIANT SHOCK RESISTANCE
INNOVATIVE INTERNAL CLAMP SYSTEM
MANUFACTURED FROM ABS



Single Cabinet Extended

CODE CS02DA
CAPACITY 9KG/9LTR/5KG CO2
EXTERNAL DIMS (WHD) 335 X 865 X 240MM
INTERNAL DIMS (WHD) 264 X 816 X 204MM
FULLY WEATHER SEALED
RESISTANT TO CHEMICALS
BRILLIANT SHOCK RESISTANCE
INNOVATIVE INTERNAL CLAMP SYSTEM
MANUFACTURED FROM ABS



Double Cabinet

CODE CS03 DA
CAPACITY 2 X 9KG/9LTR/2KG CO2
EXTERNAL DIMS (WHD) 616 X 735 X 270MM
INTERNAL DIMS (WHD) 530 X 700 X 229MM
FULLY WEATHER SEALED
RESISTANT TO CHEMICALS
BRILLIANT SHOCK RESISTANCE
INNOVATIVE INTERNAL CLAMP SYSTEM
MANUFACTURED FROM ABS
LOCKABLE
ALSO AVAILABLE IN YELLOW AND GREEN



Commander Double Lockable Cabinet

CODE CS03A DA
CAPACITY 2 X 9KG/9LTR/2KG CO2
EXTERNAL DIMS (WHD) 616 X 735 X 270MM
INTERNAL DIMS (WHD) 530 X 700 X 229MM
FULLY WEATHER SEALED
RESISTANT TO CHEMICALS
BRILLIANT SHOCK RESISTANCE
INNOVATIVE INTERNAL CLAMP SYSTEM
MANUFACTURED FROM ABS
LOCKABLE



Vehicle Extinguisher Cabinet 6kg / 9kg

CODE CS04 DA / CS05 DA
WEIGHT 2.1KG
EXTERNAL DIMS (WHD) 265X284X595MM
INTERNAL DIMS (WHD) 224X224X561MM
EXTINGUISHER DIAMETER 140/160MM
NYLON TENSION SPRING (Ø 140/160 MM)
EXTRA TENSION SPRINGS* < Ø 140 MM(Ø 140/160 MM)
NYLON HANDLE SEALABLE OR LOCKABLE
REINFORCED AND NON DEFORMABLE STRUCTURE
INTERNAL TPE SEAL AGAINST WATER AND DUST
BRACKETS CAN BE MOUNTED ON ANY SIDE
*OPTIONAL



Commander Safety Box

CODE CS60
CAPACITY 4 X 6LTR/6KG
EXTERNAL DIMS (WHD) 655 X 520 X 570MM
INTERNAL DIMS (WHD) 536 X 420 X 537MM
INTERNAL TPE SEAL AGAINST DUST AND WATER INGRESS
HIGH RESISTANCE TO: WATER AND DUST INGRESS, UV RAYS, HIGH AND LOW TEMPERATURES
SMOOTH, FLAT ROOF FOR SIGN APPLICATION
ERGONOMIC SIDE HANDLES FOR EASY CARRYING
ALSO AVAILABLE WITH COMMANDER CONTACT ALARM – SEE PAGE 42

Fire Extinguisher Signs

Fire extinguisher ID signs clearly identify the location of fire extinguishers within a building and inform users of their contents. Signs are available on white rigid plastic and can be photoluminescent to ensure visibility in all conditions.

Water ID Sign CODE 101P / 111P SIZES 75 X 200MM 150 X 100MM	Foam ID Sign CODE 102P / 112P SIZES 75 X 200MM 150 X 100MM	CO2 ID Sign CODE 103P / 113P SIZES 75 X 200MM 150 X 100MM	Powder ID Sign CODE 104P / 114P SIZES 75 X 200MM 150 X 100MM	Wet Chemical ID Sign CODE 105P / 115P SIZES 75 X 200MM 150 X 100MM	Fire Blanket ID Sign CODE 106P / 116P SIZES 75 X 200MM 150 X 100MM	MultiCHEM ID Sign CODE 107P / 117P SIZES 76 X 200MM 150 X 100MM

Emergency Escape Signs

Clearly demonstrate where the nearest emergency exit is situated to direct people safely off the premises.



**Fire Exit
(Right) Sign**

CODE
201P / 211S

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Up) Sign**

CODE
202P / 212R

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Down) Sign**

CODE
203P / 213S

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Left) Sign**

CODE
204P / 214S

SIZES
300 X 100MM
450 X 150MM



**Fire Exit
(Up Left) Sign**

CODE
207P / 217P

SIZE
300 X 100MM
450 X 150MM



**Fire Exit
(Down Right) Sign**

CODE
205P / 215S

SIZE
300 X 100MM
450 X 150MM



**Fire Exit
(Up Right) Sign**

CODE
206P / 216S

SIZE
300 X 100MM
450 X 150MM



**Fire Exit
(Down Left) Sign**

CODE
208P / 218P

SIZE
300 X 100MM
450 X 150MM



**Final Fire
Exit Sign**

CODE
301P

SIZE
300 X 150MM



**Final Fire Exit
(Man Left) Sign**

CODE
302R

SIZE
300 X 150MM



**Final
Exit Sign**

CODE
303R

SIZE
300 X 150MM



**Final Exit
(Man Left) Sign**

CODE

SIZE
300 X 150MM



**Push Bar To
Open Sign**

CODE
306P / 307R / 315S

SIZES
300 X 100MM
450 X 150MM
300 X 150MM
600 X 75MM



**Push Pad To
Open Sign**

CODE
308R

SIZE
300 X 100MM



**Fire Assembly
Point Sign**

CODE
702R 712R

SIZE
400 X 300MM
600 X 400MM



**Fire Exit
Keep Clear Sign**

CODE
309R / 310P

SIZES
450 X 150MM
200 X 200MM

Fire Action, Equipment and Door Signs

Ensure all users of the building are aware of the location of vital fire-fighting equipment and fire doors and understand exactly what action to take.



**Fire Action
Standard Sign**

CODE
401P
SIZE
150 X 200MM



**Fire Action
Picto Sign**

CODE
402P
SIZE
150 X 200MM



**Fire Alarm Call
Point Sign**

CODE
501P
SIZE
150 X 200MM



**Fire
Extinguisher Sign**

CODE
502P
SIZE
150 X 200MM



**Fire Hose
Reel Sign**

CODE
503P
SIZE
150 X 200MM



**Fire
Point Sign**

CODE
504P
SIZE
150 X 200MM



**Call Point
Picto Sign**

CODE
505P
SIZE
100 X 100MM



**Fire Extinguisher
Picto Sign**

CODE
506P
SIZE
100 X 100MM



**Fire Alarm Call
Point Sign**

CODE
511R
SIZE
200 X 300MM



**Fire
Extinguisher Sign**

CODE
512R
SIZE
200 X 300MM



**Fire Hose
Reel Sign**

CODE
503P
SIZE
200 X 300MM



**Fire
Point Sign**

CODE
514S
SIZE
200 X 300MM



**Automatic Fire
Door Sign**

CODE
901R
SIZE
100 X 100MM



**Fire Door Keep
Shut Sign**

CODE
902R
SIZE
100 X 100MM



**Fire Door Keep
Locked Shut Sign**

CODE
903R
SIZE
100 X 100MM



**Fire Door Keep
Closed Sign**

CODE
904R
SIZE
100 X 100MM

Alarms

Manually raise the alarm in times of emergency to ensure all users of the building are made aware they should vacate.



Commander Alert Site Alarm

CODE AE25
WEIGHT 670G
DIMENSIONS (WHD) 170 X 250 X 80MM*
ALARM SOUND LEVEL 115DB
12 LED SUPER BRIGHT STROBE
ABS CASE RESISTS SHOCKS AND DROPS
SIMPLE FITTING AND OPERATION
RADIO LINK MODULE AVAILABLE
IP65 RATED
*(INCLUDING ACTIVATION BUTTON AND STROBE/SIREN)



Commander Alert Site Alarm Wireless

CODE AE25/W
WEIGHT 670G
DIMENSIONS (WHD) 170 X 250 X 80MM*
ALARM SOUND LEVEL 115DB
12 LED SUPER BRIGHT STROBE
ABS CASE RESISTS SHOCKS AND DROPS
SIMPLE FITTING AND OPERATION
RADIO LINK MODULE AVAILABLE
IP65 RATED
*(INCLUDING ACTIVATION BUTTON AND STROBE/SIREN)



Smoke Alarm

CODE AE20
WEIGHT 130G
DIMENSIONS (DH) 110 X 370MM
ALARM SOUND LEVEL 85DB
TECHNOLOGY IONISATION SMOKE SENSOR
BATTERY TYPE 9V ALKALINE
WARRANTY 5 YEARS
CEILING INSTALLATION



Commander Contact Alarm

CODE AE15
WEIGHT 100G
DIMENSIONS (ØD) 87 X 87 X 43MM
ALARM SOUND LEVEL 85DB-110DB
BATTERY OPERATION 6F22 9V BATTERY
SIMPLE FITTING AND OPERATION
SUITABLE FOR USE ON THE CS60 AND ALL CABINETS OF ALARM FUNCTION



Carbon Monoxide Alarm

CODE AE23
WEIGHT 115G
DIMENSIONS (ØD) 140 X 35.5MM
ALARM SOUND LEVEL 85DB
BSI KITEMARKED EN50291
BATTERY OPERATION 3 X AA ALKALINE BATTERIES SUPPLIED AS STANDARD
WARRANTY 5 YEARS
TEST/RESET BUTTON TO ALLOW REGULAR TESTING OF ALARM FUNCTION



Rotary Alarm Bell

CODE AE01
WEIGHT 1.57KG
DIMENSIONS (ØD) 274MM X 89.4MM
ALARWM SOUND LEVEL 85DB
SUITABLE FOR USE INDOORS AND OUTDOORS
HAND-OPERATED FIRE ALARM BELL
ALUMINIUM ALLOY



Air Horn Alarm

CODE AE02
ACOUSTIC RANGE APPROX. 1500M
IDEAL FOR PROVIDING TEMPORARY COVER
IDEAL FOR CONSTRUCTION SITE APPLICATIONS

Intumescent Products

Intumescent sealants, strips and other items help slow down the spreading of fire to provide more time for evacuation of the building.



Intumescent Strip

Intumescent strip is a vital ancillary product for any door. Available as either brush pile or rubber fins, the strip works to seal around vulnerable edges of a fire door. We stock intumescent strip in a range of sizes.



Door Closers

Fire doors must be kept shut at all times to remain a crucial barrier to prevent the spread of smoke and fire. Door closers ensure a fire door is automatically closed after it's been opened. They also help to remove some the weight of this heavy door, meaning they offer a practical solution for certain settings.



Drop Seals

Fire doors require automatic drop-down seals, which provide an effective barrier against climate, noise, light, fire, smoke and insects. Once the door is closed, a plunger-like system ensures the gap between the door and flooring is closed. Choose from a range of seals suitable for glass and timber doors.



Mastic and Foam

These sealants help prevent the spread of smoke and fire. In the event of a fire, fire-resistant expanding foam fills gaps around fire doors, joints and holes in fire-rated structures, while intumescent sealant swells to create a seal.



Grilles

For easy installation in walls and fire doors, intumescent grilles allow ventilation where required and form a barrier to prevent the spread of smoke and fire. Grilles are used to provide fire dampers in ductwork.



Collars and Wraps

Pipes that penetrate fire compartment walls must be fitted with a fire prevention solution – either intumescent pipe collars or wraps. These items are fixed where the pipes intersect the wall or floor and when exposed to heat, expand to plug any gaps.

Ancillary Products

Provide support to vital fire safety equipment with our extensive selection of ancillary products, which are fully compliant with British Standards.



**Engineer's Tool Kit
(Standard)**

CODE
ST49

1KG SPRING BALANCE

20KG SPRING BALANCE

TG HEADCAP SPANNER

BRITANNIA 'C' SPANNER

ALLEN KEYS

ADJUSTABLE SPANNER

GLORIA HEADCAP 'T' BAR

FIREPOWER HEADCAP
'T' BAR

GAUGE TESTER MIJA

STANDARD ENGINEER'S
TORCH

RUBBER MALLET

NYLON VALVE BRUSH

BRASS VALVE BRUSH

200ML WD40

'O' RING REMOVAL TOOL

PETROLEUM JELLY 200G

POWDER BLOW OUT BAG



**Engineer's Tool Kit
(Advanced)**

CODE
ST50

INCLUDES STANDARD
ENGINEER'S TOOL KIT PLUS:

DIGITAL SCALE

MAGLITE® TORCH

LED INSPECTION LAMP

GAUGE TESTER EBUR WIKA

LEAK DETECTOR SPRAY

'V' CLAMP

PLASTIC FUNNEL



**Year Gauge
Indicator Dots**

CODE
ST03

SHOWS THE GAUGE HAS
BEEN TESTED

AVAILABLE IN VARIOUS
COLOURS AND CLEAR

IN ACCORDANCE WITH
BS5306



**Pull Tite
Seals**

CODE
PS09

SELF LOCKING SEAL NO
TOOLS REQUIRED

PROTECTS AGAINST
TAMPERING AND
ACCIDENTAL DISCHARGE

10 SEALS PER MAT



**Chubb Type
Pin and Discs**

CODE
PS04

PIN DIAMETER
7MM

COLOURS AVAILABLE
GREEN, BLUE, YELLOW, RED,
WHITE, ORANGE, BLACK



**Commander
Fire Blankets**

CODE
FB01 / FB02 / FB03

SIZES
1 X 1M
1.2 X 1.2M
1.8 X 1.2M

BLANKET MATERIAL
SILICONE COATED
FIBERGLASS FABRIC

OUTER CASE MATERIAL
PP CASE



**Fire Safety
Log Book**

CODE
A4LOG / A5LOG

SIZES
A4
A5

COMPLETED FOLLOWING
INSPECTIONS, TESTING AND
ANY MAINTENANCE OF FIRE
SAFETY EQUIPMENT

Ancillary Products



Service Labels

CODE ST04
DIMENSIONS 70 X 100MM
RECORD INSPECTION DETAILS
FULL COLOUR PRINT
SELF-ADHESIVE
BRANDING AVAILABLE



O-rings

CODE PP144
PIN DIAMETER 7MM
COLOURS AVAILABLE GREEN BLUE YELLOW RED WHITE ORANGE BLACK



Digital Hand-Held Scales

CODE ST08
WEIGHT 25KG X 20G
COLOURS AVAILABLE COMPLETE WITH TARE AND READING HOLD FACILITY
COLOURS AVAILABLE BATTERY OPERATED



20ltr Foam Drum Refill

CODE RP21
A FULL RANGE OF FOAM FOR ALL APPLICATIONS



20ltr Wet Chem Refill

CODE CH01
SUITABLE FOR 2KG CO2 FIRE EXTINGUISHERS



CO2 Horns 2KG / 5KG

CODE CH05
SUITABLE FOR 2KG / 5KG CO2 FIRE EXTINGUISHERS
WITH A DIRECT SWIVEL ACTION AND IS EASY TO FIT ON TO FIRE EXTINGUISHERS



Plastic Fire Bucket & Lid

CODE FBK01
CAPACITY 10LTR



T 0333 010 2000
E connect@marlowefireandsecurity.com